



- △ Innovative design COB LED surface mounted spotlight series.
- △ High purity die casting aluminum housing with fine paint finishing.
- △ Excellent ventilation to dissipate heat that ensures stable working.
- △ Professional designer optical lens gives outstanding focusing beam.
- △ Adjustable lamp head, vertical 90 degree and horizontal 360 degree.
- △ Bridgelux chips COB inside, high Ra>80/90, high lumen 150Lm/W.
- △ COB LED meets standards LM80 / EN62471 / RoHS / REACH144.
- △ High quality Isolated constant current driver, no flicker, high PF>0.90.
- △ LED driver meets standards CE / CB / TUV / BIS / CCC / SAA / FCC.
- △ Reliable quality and stable performance, low heat and low light decay.
- △ 50,000 hours life time, eco-friendly materials, up to 80% power saving.

(12W luminous intensity and lux distribution diagrams)




Model	Size	Cut Hole	Power	Beam Angle	PF	Ra	Flicker	Voltage	Lumen
CL-DL033012	Ø100x208mm	/	12W	24°/36°	>0.90	>80/90	No	90-350VAC	1100LM



- △ Innovative design COB LED surface mounted spotlight series.
- △ High purity die casting aluminum housing with fine paint finishing.
- △ Excellent ventilation to dissipate heat that ensures stable working.
- △ Professional designer optical lens gives outstanding focusing beam.
- △ Adjustable lamp head, vertical 90 degree and horizontal 360 degree.
- △ Bridgelux chips COB inside, high Ra>80/90, high lumen 150Lm/W.
- △ COB LED meets standards LM80 / EN62471 / RoHS / REACH144.
- △ High quality Isolated constant current driver, no flicker, high PF>0.90.
- △ LED driver meets standards CE / CB / TUV / BIS / CCC / SAA / FCC.
- △ Reliable quality and stable performance, low heat and low light decay.
- △ 50,000 hours life time, eco-friendly materials, up to 80% power saving.

(12W luminous intensity and lux distribution diagrams)



Model	Size	Cut Hole	Power	Beam Angle	PF	Ra	Flicker	Voltage	Lumen
CL-DL034012	Ø100x208mm	/	12W	24°/36°	>0.90	>80/90	No	90-350VAC	1100LM